

ucsd-psystem-fs UCSD p-System Filesystem

Reference Manual

Peter Miller
millerp@canb.auug.org.au

This document describes ucsd-psystem-fs version 1.1
and was prepared 11 May 2006.

This document describing the ucsd-psystem-fs package, and the ucsd-psystem-fs utility programs, are
Copyright © 2006 Peter Miller; All rights reserved.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111, USA.

	The README file	1
	Release Notes	2
	How to build ucsd-psystem-fs	3
ucsdpsys_charset(1)	UCSD p-System font builder	6
ucsdpsys_disk(1)	manipulate files on a UCSD p-System filesystem image	7
ucsdpsys_fsck(1)	verify and repair UCSD p-System filesystem images	8
ucsdpsys_fs_license(1)	GNU General Public License	9
ucsdpsys_interleave(1)	decode interleaved UCSD p-System filesystem image	14
ucsdpsys_mkfs(1)	create new UCSD p-System filesystem disk images	15
ucsdpsys_mount(1)	mount UCSD p-System filesystems	16
ucsdpsys_text(1)	translate UCSD p-System text files	18
ucsdpsys_umount(1)	unmount UCSD p-System filesystems	20

ucsdpsys_charset(1)	6	ucsdpsys charset - UCSD p-System font
ucsdpsys_charset(1)	6	ucsdpsys
ucsdpsys_mkfs(1)	15	ucsdpsys mkfs -
ucsdpsys_interleave(1)	14	ucsdpsys interleave -
ucsdpsys_mkfs(1)	15	ucsdpsys mkfs - create new UCSD p-System
ucsdpsys_disk(1)	7	ucsdpsys
ucsdpsys_text(1)	18	ucsdpsys text - translate UCSD p-System
ucsdpsys_disk(1)	7	ucsdpsys disk - manipulate
ucsdpsys_mkfs(1)	15	ucsdpsys mkfs - create new UCSD p-System
ucsdpsys_disk(1)	7	ucsdpsys disk - manipulate files on a UCSD
ucsdpsys_interleave(1)	14	ucsdpsys interleave - decode interleaved
ucsdpsys_fsck(1)	8	ucsdpsys fsck - verify and repair UCSD p-
ucsdpsys_mount(1)	16	ucsdpsys mount - mount UCSD p-System
ucsdpsys_umount(1)	20	ucsdpsys umount - unmount UCSD p-
ucsdpsys_charset(1)	6	ucsdpsys charset - UCSD p-System
ucsdpsys_fsck(1)	8	ucsdpsys
ucsdpsys_disk(1)	7	ucsdpsys disk - manipulate files on a UCSD
ucsdpsys_interleave(1)	14	ucsdpsys interleave - decode interleaved
ucsdpsys_fsck(1)	8	ucsdpsys fsck - verify and repair UCSD p-
ucsdpsys_mkfs(1)	15	ucsdpsys mkfs - create new UCSD p-System
ucsdpsys_interleave(1)	14	ucsdpsys
ucsdpsys_interleave(1)	14	ucsdpsys interleave - decode
ucsdpsys_disk(1)	7	ucsdpsys disk -
ucsdpsys_mkfs(1)	15	ucsdpsys
ucsdpsys_mount(1)	16	ucsdpsys
ucsdpsys_mount(1)	16	ucsdpsys mount -
ucsdpsys_mkfs(1)	15	ucsdpsys mkfs - create
ucsdpsys_disk(1)	7	ucsdpsys disk - manipulate files
ucsdpsys_mkfs(1)	15	ucsdpsys mkfs - create new UCSD
ucsdpsys_disk(1)	7	ucsdpsys disk - manipulate files on a UCSD
ucsdpsys_interleave(1)	14	ucsdpsys interleave - decode interleaved
ucsdpsys_fsck(1)	8	ucsdpsys fsck - verify and repair UCSD
ucsdpsys_mount(1)	16	ucsdpsys mount - mount UCSD
ucsdpsys_umount(1)	20	ucsdpsys umount - unmount UCSD

builder
charset - UCSD p-System font builder
create new UCSD p-System filesystem disk
images
decode interleaved UCSD p-System
filesystem image
disk images
disk - manipulate files on a UCSD p-System
filesystem image
files
files on a UCSD p-System filesystem image
filesystem disk images
filesystem image
filesystem image
filesystem images
filesystems
filesystems
font builder
fsck - verify and repair UCSD p-System
filesystem images
image
image
images
images
interleave - decode interleaved UCSD p-
System filesystem image
interleaved UCSD p-System filesystem
image
manipulate files on a UCSD p-System
filesystem image
mkfs - create new UCSD p-System
filesystem disk images
mount - mount UCSD p-System filesystems
mount UCSD p-System filesystems
new UCSD p-System filesystem disk images
on a UCSD p-System filesystem image
p-System filesystem disk images
p-System filesystem image
p-System filesystem image
p-System filesystem images
p-System filesystems
p-System filesystems

ucsdpsys_charset(1)	6	ucsdpsys charset - UCSD
ucsdpsys_text(1)	18	ucsdpsys text - translate UCSD
ucsdpsys_fsck(1)	8	ucsdpsys fsck - verify and
ucsdpsys_mkfs(1)	15	ucsdpsys mkfs - create new UCSD p-
ucsdpsys_disk(1)	7	ucsdpsys disk - manipulate files on a UCSD
ucsdpsys_interleave(1)	14	ucsdpsys interleave - decode interleaved
ucsdpsys_fsck(1)	8	ucsdpsys fsck - verify and repair UCSD p-
ucsdpsys_mount(1)	16	ucsdpsys mount - mount UCSD p-
ucsdpsys_umount(1)	20	ucsdpsys umount - unmount UCSD p-
ucsdpsys_charset(1)	6	ucsdpsys charset - UCSD p-
ucsdpsys_text(1)	18	ucsdpsys text - translate UCSD p-
ucsdpsys_text(1)	18	ucsdpsys text - translate UCSD p-System
ucsdpsys_text(1)	18	ucsdpsys
ucsdpsys_text(1)	18	ucsdpsys text -
ucsdpsys_charset(1)	6	
ucsdpsys_disk(1)	7	
ucsdpsys_fsck(1)	8	
ucsdpsys_interleave(1)	14	
ucsdpsys_mkfs(1)	15	
ucsdpsys_mount(1)	16	
ucsdpsys_mkfs(1)	15	ucsdpsys mkfs - create new
ucsdpsys_disk(1)	7	ucsdpsys disk - manipulate files on a
ucsdpsys_interleave(1)	14	ucsdpsys interleave - decode interleaved
ucsdpsys_fsck(1)	8	ucsdpsys fsck - verify and repair
ucsdpsys_mount(1)	16	ucsdpsys mount - mount
ucsdpsys_umount(1)	20	ucsdpsys umount - unmount
ucsdpsys_charset(1)	6	ucsdpsys charset -
ucsdpsys_text(1)	18	ucsdpsys text - translate
ucsdpsys_text(1)	18	
ucsdpsys_umount(1)	20	
ucsdpsys_umount(1)	20	ucsdpsys
ucsdpsys_umount(1)	20	ucsdpsys umount -
ucsdpsys_fsck(1)	8	ucsdpsys fsck -

p-System font builder
p-System text files
repair UCSD p-System filesystem images
System filesystem disk images
System filesystem image
System filesystem image
System filesystem images
System filesystems
System filesystems
System font builder
System text files
text files
text - translate UCSD p-System text files
translate UCSD p-System text files
ucsdpsys charset - UCSD p-System font
builder
ucsdpsys disk - manipulate files on a UCSD
p-System filesystem image
ucsdpsys fsck - verify and repair UCSD p-
System filesystem images
ucsdpsys interleave - decode interleaved
UCSD p-System filesystem image
ucsdpsys mkfs - create new UCSD p-System
filesystem disk images
ucsdpsys mount - mount UCSD p-System
filesystems
UCSD p-System filesystem disk images
UCSD p-System filesystem image
UCSD p-System filesystem image
UCSD p-System filesystem images
UCSD p-System filesystems
UCSD p-System filesystems
UCSD p-System filesystems
UCSD p-System font builder
UCSD p-System text files
ucsdpsys text - translate UCSD p-System
text files
ucsdpsys umount - unmount UCSD p-
System filesystems
umount - unmount UCSD p-System
filesystems
unmount UCSD p-System filesystems
verify and repair UCSD p-System filesystem
images

NAME

ucsd-psystem-fs – UCSD p-System file system

DESCRIPTION

The *ucsd-psystem-fs* package is a collection of tools for manipulating and mounting UCSD p-System disk images.

ARCHIVE SITE

The latest version of *ucsd-psystem-fs* is available on the Web from:

URL:	http://ucsd-psystem-fs.sourceforge.net/	
File:	ucsd-psystem-fs.html	# the ucsd-psystem-fs page
File:	ucsd-psystem-fs-1.1.README	# Description, from the tar file
File:	ucsd-psystem-fs-1.1.lsm	# Description, LSM format
File:	ucsd-psystem-fs-1.1.spec	# RedHat package specification
File:	ucsd-psystem-fs-1.1.tar.gz	# the complete source
File:	ucsd-psystem-fs-1.1.pdf	# Reference Manual

BUILDING ucsd-psystem-fs

Full instructions for building *ucsd-psystem-fs* may be found in the *BUILDING* file included in this distribution.

COPYRIGHT

ucsd-psystem-fs version 1.1

Copyright © 2006 Peter Miller

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111, USA.

It should be in the *LICENSE* file included with this distribution.

AUTHOR

Peter Miller	E-Mail:	millerp@canb.auug.org.au
/\/*	WWW:	http://www.canb.auug.org.au/~millerp/

RELEASE NOTES

This section details the various features and bug fixes of the various releases.

Version 1.1 (2006-Apr-11)

- The *ucsdpsys_mount*(1) is used to mount a UCSD p-System filesystem disk image as a Linux file system. See *ucsdpsys_mount*(1) for more information.
- The *ucsdpsys_umount*(1) is used to unmount a filesystem mounted by the *ucsdpsys_mount*(1) command. See *ucsdpsys_umount*(1) for more information.
- The *ucsdpsys_mkfs*(1) is used to create a new empty UCSD p-System filesystem disk image. See *ucsdpsys_mkfs*(1) for more information.
- The *ucsdpsys_fsck*(1) is used to verify and repair a UCSD p-System filesystem disk image. See *ucsdpsys_fsck*(1) for more information.
- The *ucsdpsys_disk*(1) is used to list, extract, insert and remove files from a UCSD p-System filesystem disk image, without mounting it. See *ucsdpsys_disk*(1) for more information.
- The *ucsdpsys_text*(1) is used to convert text files from the UCSD p-System format to a Unix text file, and back again. See *ucsdpsys_text*(1) for more information.

NAME

How to build ucsd-psystem-fs

BEFORE YOU START

There are a few pieces of software you may want to fetch and install before you proceed with your installation of ucsd-psystem-fs.

FUSE The *ucsd-psystem-fs* package depends on the FUSE (file system in user space) package. If it is not available on your system, ucsd-psystem-fs will not work on your system. At the moment, that means Linux only.
<http://fuse.sourceforge.net/>

GNU Groff

The documentation for the *ucsd-psystem-fs* package was prepared using the GNU Groff package (version 1.14 or later). This distribution includes full documentation, which may be processed into PostScript or DVI files at install time – if GNU Groff has been installed.

SITE CONFIGURATION

The **ucsd-psystem-fs** package is configured using the *configure* program included in this distribution.

The *configure* shell script attempts to guess correct values for various system-dependent variables used during compilation, and creates the *Makefile* and *lib/config.h* files. It also creates a shell script *config.status* that you can run in the future to recreate the current configuration.

Normally, you just *cd* to the directory containing *ucsd-psystem-fs*'s source code and then type

```
% ./configure
...lots of output...
%
```

Running *configure* takes a minute or two. While it is running, it prints some messages that tell what it is doing. If you don't want to see the messages, run *configure* using the quiet option; for example,

```
% ./configure --quiet
%
```

To compile the **ucsd-psystem-fs** package in a different directory from the one containing the source code, you must use a version of *make* that supports the *VPATH* variable, such as *GNU make*. Change directory to the directory where you want the object files and executables to go and run the *configure* script. The *configure* script automatically checks for the source code in the directory that *configure* is in and in *..* (the parent directory). If for some reason *configure* is not in the source code directory that you are configuring, then it will report that it can't find the source code. In that case, run *configure* with the option *--srcdir=DIR*, where *DIR* is the directory that contains the source code.

By default, *configure* will arrange for the *make install* command to install the **ucsd-psystem-fs** package's files in */usr/local/bin*, and */usr/local/man*. There are options which allow you to control the placement of these files.

--prefix=PATH

This specifies the path prefix to be used in the installation. Defaults to */usr/local* unless otherwise specified.

--exec-prefix=PATH

You can specify separate installation prefixes for architecture-specific files. Defaults to *\${prefix}* unless otherwise specified.

--bindir=PATH

This directory contains executable programs. On a network, this directory may be shared between machines with identical hardware and operating systems; it may be mounted read-only. Defaults to *\${exec_prefix}/bin* unless otherwise specified.

--mandir=PATH

This directory contains the on-line manual entries. On a network, this directory may be shared between all machines; it may be mounted read-only. Defaults to *\${prefix}/man* unless otherwise

specified.

The *configure* script ignores most other arguments that you give it; use the `--help` option for a complete list.

On systems that require unusual options for compilation or linking that the *ucsd-psystem-fs* package's *configure* script does not know about, you can give *configure* initial values for variables by setting them in the environment. In Bourne-compatible shells, you can do that on the command line like this:

```
$ CXX='g++ -traditional' LIBS=-lposix ./configure
...lots of output...
$
```

Here are the *make* variables that you might want to override with environment variables when running *configure*.

Variable: CXX

C++ compiler program. The default is *c++*.

Variable: CPPFLAGS

Preprocessor flags, commonly defines and include search paths. Defaults to empty. It is common to use `CPPFLAGS=-I/usr/local/include` to access other installed packages.

Variable: INSTALL

Program to use to install files. The default is *install* if you have it, *cp* otherwise.

Variable: LIBS

Libraries to link with, in the form `-lfoo -lbar`. The *configure* script will append to this, rather than replace it. It is common to use `LIBS=-L/usr/local/lib` to access other installed packages.

If you need to do unusual things to compile the package, the author encourages you to figure out how *configure* could check whether to do them, and mail diffs or instructions to the author so that they can be included in the next release.

BUILDING UCSD-PSYSTEM-FS

All you should need to do is use the

```
% make
...lots of output...
%
```

command and wait. When this finishes you should see a directory called *bin* containing several programs.

If you have GNU Groff installed, the build will also create a *etc/reference.ps* file. This contains the README file, this BUILDING file, and all of the man pages.

You can remove the program binaries and object files from the source directory by using the

```
% make clean
...lots of output...
%
```

command. To remove all of the above files, and also remove the *Makefile* and *lib/config.h* and *config.status* files, use the

```
% make distclean
...lots of output...
%
```

command.

The file *etc/configure.in* is used to create *configure* by a GNU program called *autoconf*. You only need to know this if you want to regenerate *configure* using a newer version of *autoconf*.

TESTING UCSD-PSYSTEM-FS

The *ucsd-psystem-fs* package comes with a test suite. To run this test suite, use the command

```
% make sure
...lots of output...
Passed All Tests
%
```

The tests take a few seconds each, with a few very fast, and a couple very slow, but it varies greatly depending on your CPU.

If all went well, the message

```
Passed All Tests
```

should appear at the end of the make.

INSTALLING UCSD-PSYSTEM-FS

As explained in the *SITE CONFIGURATION* section, above, the *ucsd-psystem-fs* package is installed under the */usr/local* tree by default. Use the `--prefix=PATH` option to *configure* if you want some other path. More specific installation locations are assignable, use the `--help` option to *configure* for details.

All that is required to install the *ucsd-psystem-fs* package is to use the

```
% make install
...lots of output...
%
```

command. Control of the directories used may be found in the first few lines of the *Makefile* file and the other files written by the *configure* script; it is best to reconfigure using the *configure* script, rather than attempting to do this by hand.

GETTING HELP

If you need assistance with the *ucsd-psystem-fs* package, please do not hesitate to contact the author at

```
Peter Miller <millerp@canb.auug.org.au>
```

Any and all feedback is welcome.

When reporting problems, please include the version number given by the

```
% ucsdpsys_mount -V
ucsdpsys_mount version 1.1.D001
...warranty disclaimer...
%
```

command. Please do not send this example; run the program for the exact version number.

COPYRIGHT

ucsd-psystem-fs version 1.1

Copyright © 2006 Peter Miller

The *ucsd-psystem-fs* package is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

It should be in the *LICENSE* file included with this distribution.

AUTHOR

Peter Miller E-Mail: millerp@canb.auug.org.au

/\ /\ * WWW: http://www.canb.auug.org.au/~millerp/

NAME

ucsdpsys_charset – UCSD p-System font builder

SYNOPSIS

ucsdpsys_charset -d [*input.binary.file* [*output.text.fileP*]]

ucsdpsys_charset -e [*input.text.file* [*output.binary.fileP*]]

ucsdpsys_charset -V

DESCRIPTION

The *ucsdpsys_charset* program is used to decode and encode font characters for use as the *[CW]SYSTEM.CHARSET* file.

OPTIONS

The following options are understood:

-d Decode the binary font file into a text file which can be edited.

-e Encode a text file representation of the glyphs of the font into the binary for used for the *SYSTEM.CHARSET* file.

-V Print the version of the *ucsdpsys_charset* program being executed.

All other options will produce a diagnostic error.

EXIT STATUS

The *ucsdpsys_charset* command will exit with a status of 1 on any error. The *ucsdpsys_charset* command will only exit with a status of 0 if there are no errors.

COPYRIGHT

ucsdpsys_charset version 1.1

Copyright © 2006 Peter Miller

The *ucsdpsys_charset* program comes with ABSOLUTELY NO WARRANTY; for details use the '*ucsdpsys_charset -VERsion License*' command. This is free software and you are welcome to redistribute it under certain conditions; for details use the '*ucsdpsys_charset -VERsion License*' command.

AUTHOR

Peter Miller E-Mail: millerp@canb.auug.org.au

^/* WWW: http://www.canb.auug.org.au/~millerp/

NAME

ucsdpsys_disk – manipulate files on a UCSD p-System filesystem image

SYNOPSIS

```
ucsdpsys_disk -f disk-image -l
ucsdpsys_disk -f disk-image -g files.to.get...
ucsdpsys_disk -f disk-image -p files.to.put...
ucsdpsys_disk -f disk-image -r files.to.remove...
ucsdpsys_disk -f disk-image -V
```

DESCRIPTION

The *ucsdpsys_disk* program is used to manipulate the contents of a UCSD p-System filesystem disk image.

OPTIONS

The following options are understood:

-f filename

The name of the file containing the UCSD p-System filesystem disk image.

-g filename...

Get the named files from the disk image and write them to Unix, using the same file name. Note that text file formats will *not* be translated.

-p filename...

Put the named files into the disk image, reading from the Unix file of the same name. Note that text file formats will *not* be translated.

-r filename...

Remove the named files from the filesystem image.

-V

Print the version of the *ucsdpsys_disk* program being executed.

All other options will produce a diagnostic error.

EXIT STATUS

The *ucsdpsys_disk* command will exit with a status of 1 on any error. The *ucsdpsys_disk* command will only exit with a status of 0 if there are no errors.

SEE ALSO

ucsdpsys_mkfs(1)
create a new disk image

ucsdpsys_mount(1)
mount a disk image

ucsdpsys_text(1)
translate text file formats

COPYRIGHT

ucsdpsys_disk version 1.1
Copyright © 2006 Peter Miller

The *ucsdpsys_disk* program comes with ABSOLUTELY NO WARRANTY; for details use the '*ucsdpsys_disk -VERsion License*' command. This is free software and you are welcome to redistribute it under certain conditions; for details use the '*ucsdpsys_disk -VERsion License*' command.

AUTHOR

Peter Miller E-Mail: millerp@canb.auug.org.au
^/* WWW: http://www.canb.auug.org.au/~millerp/

NAME

ucsdpsys_fsck – verify and repair UCSD p-System filesystem images

SYNOPSIS

ucsdpsys_fsck [*option...*] *disk-image*
ucsdpsys_fsck -V

DESCRIPTION

The *ucsdpsys_fsck* program is used to verify and repair UCSD p-System filesystem disk images.

OPTIONS

The following options are understood:

-V Print the version of the *ucsdpsys_fsck* program being executed.

All other options will produce a diagnostic error.

EXIT STATUS

The *ucsdpsys_fsck* command will exit with a status of 1 on any error. The *ucsdpsys_fsck* command will only exit with a status of 0 if there are no errors.

SEE ALSO

ucsdpsys_disk(1)
 manipulate a disk image

ucsdpsys_mount(1)
 mount a disk image

COPYRIGHT

ucsdpsys_fsck version 1.1
Copyright © 2006 Peter Miller

The *ucsdpsys_fsck* program comes with ABSOLUTELY NO WARRANTY; for details use the '*ucsdpsys_fsck -VERsion License*' command. This is free software and you are welcome to redistribute it under certain conditions; for details use the '*ucsdpsys_fsck -VERsion License*' command.

AUTHOR

Peter Miller E-Mail: millerp@canb.auug.org.au
^/* WWW: http://www.canb.auug.org.au/~millerp/

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.

59 Temple Place, Suite 330, Boston, MA 02111, USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software -- to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.
- b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.
- c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

- a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on

consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

one line to give the program's name and a brief idea of what it does.

Copyright (C) 19yy name of author

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111, USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) 19yy name of author

Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type 'show w'. This is free software, and you are welcome to redistribute it under certain conditions; type 'show c' for details.

The hypothetical commands 'show w' and 'show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than 'show w' and 'show c'; they could even be mouse-clicks or menu items -- whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program 'Gnomovision' (which makes passes at compilers) written by James Hacker.

signature of Ty Coon, 1 April 1989

Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

NAME

ucsdpsys_interleave – decode interleaved UCSD p-System filesystem image

SYNOPSIS

ucsdpsys_interleave -d -Tname infile outfile

ucsdpsys_interleave -e -Tname infile outfile

ucsdpsys_interleave -V

DESCRIPTION

The *ucsdpsys_interleave* program is used to read a UCSD p-System filesystem image and decode it into a new uninterleaved filesystem image file. It is also possible to do the reverse.

OPTIONS

The following options are understood:

- D** Increase debug level. Only of interest to developers.
- d** read a UCSD p-System filesystem image and decode it into a new **un**interleaved filesystem image file.
- e** read a UCSD p-System filesystem image and encode it into a new interleaved filesystem image file.
- T name**
This option is used to specify the type of interleaving in question. Known formats are:
 apple The symmetric interleaving used by the Apple][Pascal system.
 pdp The offset and asymmetric interleaved format used by the PDP11 (?) system.
 No interleave format guessing is performed by this program, however the *ucsdpsys_mount*(1) and *ucsdpsys_disk*(1) programs will automatically detect common interleaving formats.
- V** Print the version of the *ucsdpsys_interleave* program being executed.

All other options will produce a diagnostic error.

EXIT STATUS

The *ucsdpsys_interleave* command will exit with a status of 1 on any error. The *ucsdpsys_interleave* command will only exit with a status of 0 if there are no errors.

COPYRIGHT

ucsdpsys_interleave version 1.1

Copyright © 2006 Peter Miller

The *ucsdpsys_interleave* program comes with ABSOLUTELY NO WARRANTY; for details use the '*ucsdpsys_interleave -VERsion License*' command. This is free software and you are welcome to redistribute it under certain conditions; for details use the '*ucsdpsys_interleave -VERsion License*' command.

AUTHOR

Peter Miller E-Mail: millerp@canb.auug.org.au
 ^\^* WWW: http://www.canb.auug.org.au/~millerp/

NAME

ucsdpsys_mkfs – create new UCSD p-System filesystem disk images

SYNOPSIS

ucsdpsys_mkfs [*option...*] *filename*
ucsdpsys_mkfs -V

DESCRIPTION

The *ucsdpsys_mkfs* program is used to create new UCSD p-System disk image files.

Only Apple][Pascal disks are understood at present. It is simple to add more disk formats.

OPTIONS

The following options are understood:

-B *number*

This option may be used to specify the size of the disk image, in kilobytes (KB = 1024 bytes). Defaults to 140 if not specified.

-D Increase debugging level. Only of interest to developers.**-i** Interleave the sectors on each 16-sector track. The default is a sequential non-interleaved sector layout.**-L** *string*

This option may be used to specify the name of the volume. Defaults to something random, but probably unique, starting with "V". There is a size limit of 7 characters, your label will be truncated if it is longer than this.

-t This option may be used to ask for two copies of the directory meta-data to be stored, not just one. This will not be used by *ucsdpsys_fsck*(1), but it will be kept up-to-date by all of the disk access methods.**-V** Print the version of the *ucsdpsys_mkfs* program being executed.

All other options will produce a diagnostic error.

EXIT STATUS

The *ucsdpsys_mkfs* command will exit with a status of 1 on any error. The *ucsdpsys_mkfs* command will only exit with a status of 0 if there are no errors.

SEE ALSO

ucsdpsys_fsck(1)
 check a disk image

ucsdpsys_mount(1)
 mount a disk image

COPYRIGHT

ucsdpsys_mkfs version 1.1
 Copyright © 2006 Peter Miller

The *ucsdpsys_mkfs* program comes with ABSOLUTELY NO WARRANTY; for details use the '*ucsdpsys_mkfs -VERSion License*' command. This is free software and you are welcome to redistribute it under certain conditions; for details use the '*ucsdpsys_mkfs -VERSion License*' command.

AUTHOR

Peter Miller E-Mail: millerp@canb.auug.org.au
 ^\^* WWW: http://www.canb.auug.org.au/~millerp/

NAME

ucsdpsys_mount – mount UCSD p-System filesystems

SYNOPSIS

ucsdpsys_mount [*option...*] *filename directory*
ucsdpsys_mount -V

DESCRIPTION

The *ucsdpsys_mount* program is used to mount files containing UCSD p-System disk images as Linux file systems.

Disk Formats

At present, only the Apple][Pascal disk format is understood, however it is simple to add more formats in future.

The disk image can be interleaved or non-interleaved, and the code will automatically adjust.

Umount When Finish

To umount the file system when you are done with it, use the
 fusermount -u directory
 command.

Concurrent Writes

The original p-System had difficulty writing to more than one file at a time. This file system uses the Buffer Gap algorithm (a common implementation for text editors) to establish a gap for write to be performed within, compacting file automatically when necessary. While you have a single file open for writing, this is very efficient.

If you have two files open for writing, this file system can cope, but the constant block shuffling to obtain gaps in which to write two (or more) files simultaneously will affect performance.

OPTIONS

The following options are understood:

- D** Turn on internal debugging. Specifying this option more than once increases the verbosity.
- d** Turn on FUSE (libfuse) debugging. Only interesting to *ucsdpsys_mount(1)* developers. Implies the **-f** options.
- f** Execute the filesystem in the foreground. Usually a daemon process is spawned, and the *ucsdpsys_mount(1)* command returns immediately.
- o string** One or *mount(1)* options, separated by commas. This option may be given more than once.
- r** Mount the file system read-only.
- V** Print the version of the *ucsdpsys_mount* program being executed.

All other options will produce a diagnostic error.

EXIT STATUS

The *ucsdpsys_mount* command will exit with a status of 1 on any error. The *ucsdpsys_mount* command will only exit with a status of 0 if there are no errors.

SEE ALSO

fusermount(1)
 mount FUSE file systems

ucsdpsys_fsck(1)
 Check the integrity of UCSD p-System filesystem disk images.

ucsdpsys_mkfs(1)
 create new empty UCSD p-System filesystem disk images.

ucsdpsys_umount(1)
unmount UCSD p-System filesystems

COPYRIGHT

ucsdpsys_mount version 1.1
Copyright © 2006 Peter Miller

The *ucsdpsys_mount* program comes with ABSOLUTELY NO WARRANTY; for details use the '*ucsdpsys_mount -VERSion License*' command. This is free software and you are welcome to redistribute it under certain conditions; for details use the '*ucsdpsys_mount -VERSion License*' command.

AUTHOR

Peter Miller	E-Mail:	millerp@canb.auug.org.au
^^*	WWW:	http://www.canb.auug.org.au/~millerp/

NAME

ucsdpsys_text – translate UCSD p-System text files

SYNOPSIS

ucsdpsys_text -d [*filename...*]

ucsdpsys_text -e [*filename...*]

ucsdpsys_text -V

DESCRIPTION

The *ucsdpsys_text* program is used to translate UCSD p-System text files to and from Unix text files.

If no files are named on the command line, the standard input will be translated and written on the standard output.

Any files named on the command line will be translated *in situ*. A temporary output file will be in the same directory as each file being translated; the file system will need enough extra space to be able to hold the temporary files, until they are moved back over the input files. No backup copies of the inputs are kept.

The results are undefined if you attempt to use this command on binary data files.

OPTIONS

The following options are understood:

-d This option is used to translate files from UCSD p-System text format to Unix text format.

-e This option is used to translate files from Unix text format to UCSD p-System text format.

-V Print the version of the *ucsdpsys_text* program being executed.

All other options will produce a diagnostic error.

EXIT STATUS

The *ucsdpsys_text* command will exit with a status of 1 on any error. The *ucsdpsys_text* command will only exit with a status of 0 if there are no errors.

UCSD P-SYSTEM TEXT FILE FORMAT

The format of a textfile is as follows:

- There are two blocks (1024 bytes) of header information at the beginning of the file. This information is used by the Pascal Editor. The Pascal system creates the header page when a user program opens a textfile. The header page is transferred only during disk-to-disk transfers; transfers to character devices, such as the console or printer, always omit the header page.
- The rest of the file consists of two-block pages. Each page contains lines of text, separated from each other by RETURN characters (ASCII 13). No line ever crosses a page boundary; thus a page contains only whole lines. After the last line on a page, the remainder of the page is filled with NUL characters (ASCII 00). READ and READLN skip the NUL characters, and WRITE and WRITELN provide them automatically. Thus this page formatting is normally invisible to a Pascal program.
- A sequence of leading spaces in a line may be compressed to a DLE-blank code. This code consists of a DLE control character (ASCII 16) followed by one byte containing the number of spaces to indent plus 32 (decimal). Using this code saves a considerable amount of space in files where indentation occurs frequently. The Editor is the main creator of DLE-blank codes; it usually outputs a DLE-blank code where a sequence of spaces occurs at the beginning of a line. However, the DLE-blank code is optional; some lines may have it, and others may have space characters instead. Also, a line with no indentation may or may not be preceded by a DLE character and an indent code value of 32 (meaning 0 indentation).

COPYRIGHT

ucsdpsys_text version 1.1

Copyright © 2006 Peter Miller

The *ucsdpsys_text* program comes with ABSOLUTELY NO WARRANTY; for details use the '*ucsdpsys_text -VERSION License*' command. This is free software and you are welcome to redistribute it under certain conditions; for details use the '*ucsdpsys_text -VERSION License*' command.

AUTHOR

Peter Miller
^/*

E-Mail: millerp@canb.auug.org.au
WWW: <http://www.canb.auug.org.au/~millerp/>

NAME

ucsdpsys_umount – unmount UCSD p-System filesystems

SYNOPSIS

ucsdpsys_umount *mount-point*

ucsdpsys_umount -V

DESCRIPTION

The *ucsdpsys_umount* program is used to unmount a file system mounted by the *ucsdpsys_mount(1)* command.

OPTIONS

The following options are understood:

-V

Print the version of the *ucsdpsys_umount* program being executed.

All other options will produce a diagnostic error.

EXIT STATUS

The *ucsdpsys_umount* command will exit with a status of 1 on any error. The *ucsdpsys_umount* command will only exit with a status of 0 if there are no errors.

SEE ALSO

fusermount(1)

umount FUSE file systems

ucsdpsys_mount(1)

mount UCSD p-System filesystem disk images.

COPYRIGHT

ucsdpsys_umount version 1.1

Copyright © 2006 Peter Miller

The *ucsdpsys_umount* program comes with ABSOLUTELY NO WARRANTY; for details use the '*ucsdpsys_umount -VERSion License*' command. This is free software and you are welcome to redistribute it under certain conditions; for details use the '*ucsdpsys_umount -VERSion License*' command.

AUTHOR

Peter Miller E-Mail: millerp@canb.auug.org.au

^/* WWW: http://www.canb.auug.org.au/~millerp/